

Angle seat globe valves, metal



GEMÜ 507

2/2-way globe valve, metal, manually operated with plastic handwheel

DN	Operating pressure	Connection	Valve body material	Seat seal
6 to 80	0 to 25 bar *	Butt weld spigots Threaded connections Clamp connections Flanges Different standards and designs available.	Stainless steel 1.4435, 1.4408	PTFE PEEK



GEMÜ 505

2/2-way globe valve, metal, manually operated with plastic handwheel

DN	Operating pressure	Connection	Valve body material	Seat seal
8 to 80	0 to 10 bar *	Butt weld spigots Different standards and designs available.	Stainless steel 1.4435	PTFE



GEMÜ 555

2/2-way globe valve, metal, pneumatically operated, stainless steel piston actuator
Control function: Normally closed (NC)

DN	Operating pressure	Connection	Valve body material	Seat seal
8 to 80	0 to 10 bar *	Butt weld spigots Different standards and designs available.	Stainless steel 1.4435	PTFE



GEMÜ 554

2/2-way globe valve, metal, pneumatically operated, plastic piston actuator
Control function: Normally closed (NC), Normally open (NO), Double acting (DA)

DN	Operating pressure	Connection	Valve body material	Seat seal
6 to 80	0 to 25 bar *	Butt weld spigots Threaded connections Clamp connections Flanges Different standards and designs available.	Cast bronze Stainless steel 1.4435, 1.4408	PTFE EPDM NBR

* dependent on nominal size and design



GEMÜ 550

2/2-way globe valve, metal, pneumatically operated, stainless steel piston actuator

Control function: Normally closed (NC), Normally open (NO), Double acting (DA)

DN	Operating pressure	Connection	Valve body material	Seat seal
6 to 80	0 to 25 bar *	Butt weld spigots Threaded connections Clamp connections Flanges Different standards and designs available.	Stainless steel 1.4435, 1.4408	PTFE EPDM NBR Steel



GEMÜ 514

2/2-way globe valve, metal, pneumatically operated, aluminium piston actuator

Control function: Normally closed (NC), Normally open (NO), Double acting (DA)

DN	Operating pressure	Connection	Valve body material	Seat seal
10 to 80	0 to 25 bar *	Butt weld spigots Threaded connections Flanges Different standards and designs available.	Cast bronze Stainless steel 1.4435, 1.4408	PTFE EPDM NBR Steel

* dependent on nominal size and design