

# Ball valves, plastic



## GEMÜ 717

2/2, 3/2-way ball valve, plastic, manually operated

DN	Operating pressure	Connection	Valve body material	Seal material
15 to 100	0 to 10 bar *	Solvent cement/ welded sockets (DIN)	PVC-U, grey PP PVDF	Seat: PTFE/ O-rings: EPDM Seat: PTFE/ O-rings: FPM



## GEMÜ 710

2/2, 3/2-way ball valve, plastic, pneumatically operated

Control function: Normally closed (NC), Double acting (DA)

DN	Operating pressure	Connection	Valve body material	Seal material
15 to 100	0 to 10 bar *	Solvent cement/ welded sockets (DIN)	PVC-U, grey PP	Seat: PTFE/ O-rings: EPDM Seat: PTFE/ O-rings: FPM



## GEMÜ 723

2/2, 3/2-way ball valve, plastic, motorized

DN	Operating pressure	Connection	Voltage	Valve body material	Seal material
15 to 100	0 to 10 bar *	Solvent cement/ welded sockets (DIN)	12, 24 VDC 12, 24, 100-250 VAC 50/60 Hz	PVC-U, grey PP PVDF	Seat: PTFE/ O-rings: EPDM Seat: PTFE/ O-rings: FPM

\* dependent on operating temperature

# Ball valves, metal



## GEMÜ 707

2/2-way ball valve, metal, 2-piece body, manually operated

Lockable hand lever

DN	Operating pressure	Connection	Valve body material	Seal material
8 to 50	0 to 63 bar *	Threaded sockets	Stainless steel 1.4408 (body) 1.4401 (ball)	PTFE



## GEMÜ 711

2/2, 3/2-way ball valve, metal, 3-piece body with top flange, manually operated

Lockable hand lever

DN	Operating pressure	Connection	Valve body material	Seal material
8 to 100	0 to 63 bar *	Threaded sockets Spigots Flanges Different standards and designs available.	Stainless steel 1.4408 (body) 1.4401 (ball) CF3M (body) 316L (ball)	PTFE



## GEMÜ 712

2/2, 3/2-way ball valve, metal, 3-piece body, manually operated

Lockable hand lever

DN	Operating pressure	Connection	Valve body material	Seal material
8 - 100	0 to 63 bar *	Threaded sockets Spigots Flanges Different standards and designs available.	Stainless steel 1.4408 (body) 1.4401 (ball)	PTFE



## GEMÜ 740 Sanitary

2/2-way ball valve, metal, 3-piece body, manually operated

Lockable hand lever

DN	Operating pressure	Connection	Valve body material	Seal material
15 to 100	0 to 63 bar *	Butt weld spigots Spigots Clamps Different standards and designs available.	Stainless steel CF3M (316L) (body) CF3M (316L) (ball)	TFM™ PTFE

\* dependent on operating temperature and nominal size



### GEMÜ 762

2/2-way ball valve, metal, one-piece body with top flange, manually operated  
Lockable hand lever

DN	Operating pressure	Connection	Valve body material	Seal material
15 to 100	0 to 16 bar *	Flanges	Stainless steel 1.4408 (body) 1.4401 (ball)	PTFE



### GEMÜ 741 Sanitary

2/2-way ball valve, metal, 3-piece body with top flange, pneumatically operated

DN	Operating pressure	Connection	Valve body material	Seal material
15 to 100	0 to 63 bar *	Butt weld spigots Spigots Clamps Different standards and designs available.	Stainless steel CF3M (316L) (body) CF3M (316L) (ball)	TFM™ PTFE



### GEMÜ 751

2/2, 3/2-way ball valve, metal, 3-piece body with top flange, pneumatically operated

DN	Operating pressure	Connection	Valve body material	Seal material
8 to 100	0 to 63 bar *	Threaded sockets Spigots Flanges Different standards and designs available.	Stainless steel 1.4408 (body) 1.4401 (ball) CF3M (body) 316L (ball)	PTFE



### GEMÜ 761

2/2-way ball valve, metal, one-piece body with top flange, pneumatically operated

DN	Operating pressure	Connection	Valve body material	Seal material
15 to 100	0 to 16 bar *	Flanges	Stainless steel 1.4408 (body) 1.4401 (ball)	PTFE

\* dependent on operating temperature and nominal size

# Ball valves, metal



## GEMÜ 748 Sanitary

2/2-way ball valve, metal, 3-piece body with top flange, motorized

DN	Operating pressure	Connection	Voltage	Valve body material	Seal material
15 to 100	0 to 63 bar *	Butt weld spigots Spigots Clamps Different standards and designs available.	12 V / 24 V 100-250 V	Stainless steel CF3M (316L) (body) CF3M (316L) (ball)	TFM™ PTFE



## GEMÜ 728 Sanitary

2/2-way ball valve, metal, 3-piece body with top flange, motorized

DN	Operating pressure	Connection	Voltage	Valve body material	Seal material
15 to 100	0 to 63 bar *	Threaded sockets Spigots Flanges Different standards and designs available.	12, 24 VDC 24, 120, 230 VAC 50/60 Hz	Stainless steel 1.4408 (body) 1.4401 (ball) CF3M (body) 316L (ball)	PTFE



## GEMÜ 768 Sanitary

2/2-way ball valve, metal, one-piece body with top flange, motorized

DN	Operating pressure	Connection	Voltage	Valve body material	Seal material
15 to 100	0 to 63 bar *	Flanges	12, 24 VDC 24, 120, 230 VAC 50/60 Hz	Stainless steel 1.4408 (body) 1.4401 (ball)	PTFE

\* dependent on operating temperature and nominal size