

Control valves, plastic and metal



GEMÜ 565

2/2-way globe valve, plastic and metal, pneumatically operated
Stainless steel piston actuator, control function: Normally closed (NC)

DN	Operating pressure	Connection	Valve body material	Seat seal
3 to 15	0 to 6 bar *	Threaded sockets DIN ISO 228 Threaded spigots Union ends with insert Clamp connections	PVC-U, grey PVDF	FPM EPDM



GEMÜ 566

2/2-way control valve, metal, various actuation types
Stainless steel operator (manual, pneumatic), plastic actuator (motorized)

DN	Operating pressure	Connection	Valve body material	Seat seal
8 to 15	0 to 6 bar *	Threaded sockets	1.4435 (investment casting)	FPM EPDM



GEMÜ 563

2/2-way globe valve, plastic, motorized, plastic actuator
With/without integr. positioner/process controller, operating time 17 sec./45 sec.

DN	Operating pressure	Connection	Voltage	Valve body material	Seat seal
3 to 15	0 to 6 bar *	Threaded sockets DIN ISO 228	24 VAC 120 VAC 230 VAC 50/60Hz	PVC-U, grey PVDF	FPM EPDM



GEMÜ 548 SideStep®

2/2-way globe valve, metal, motorized, plastic actuator
Open/Close or control actuator with various options available

DN	Operating pressure	Connection	Voltage	Valve body material	Seat seal
25 to 80	0 to 25 bar *	Butt weld spigots, threaded connections Different standards and designs available.	24 VAC 120 VAC 230 VAC 50/60Hz	Cast bronze Stainless steel 1.4435, 1.4408	FPM EPDM PTFE

* dependent on nominal size and design