

# Pilot solenoid valves, plastic



## GEMÜ 0322/0324

3/2-way solenoid valve, plastic, directly controlled

0322 single mounting & battery design, 0324 direct mounting

Control function: Normally closed

DN	Operating pressure	Connection	Voltage	Valve body material	Seal material
2	0 to 10 bar	Threaded sockets	24 V DC 24 V AC 120 V AC 230 V AC 50/60Hz	PA	FPM



## GEMÜ 332/334

3/2-way solenoid valve, plastic, directly controlled

332 battery design, 334 direct mounting

Control function: Normally closed

DN	Operating pressure	Connection	Voltage	Valve body material	Seal material
1	0 to 10 bar	Threaded sockets	24 V DC 24 V AC 120 V AC 230 V AC 50/60Hz	PBTP	FPM

# Pilot solenoid valves, metal



## GEMÜ 8303

3/2-way solenoid valve, metal, directly controlled

Control function: Normally closed

DN	Operating pressure	Air output	Connection	Voltage	Valve body material	Seal material
2	1 to 10 bar	1.2 m <sup>3</sup> /h at 6 bar	Threaded sockets	24 V DC 24 V AC 110 V AC 230 V AC 50Hz	Brass Stainless steel 1.4581	NBR



## GEMÜ 8357

3/2-way solenoid valve, metal, servo assisted

Control function: Normally closed

DN	Operating pressure	Air output	Connection	Voltage	Valve body material	Seal material
6	1 to 10 bar	1.2 m <sup>3</sup> /h at 6 bar	Threaded sockets	24 V DC 24 V AC 230 V AC 50Hz	Aluminium	NBR



## GEMÜ 8458

5/2-way solenoid valve, metal, servo assisted

Control function: Normally closed

DN	Operating pressure	Air output	Connection	Voltage	Valve body material	Seal material
6	1 to 10 bar	1.2 m <sup>3</sup> /h at 6 bar	Threaded sockets	24 V DC 24 V AC 230 V AC 50Hz	Aluminium	NBR



## GEMÜ 8505

4/2-way solenoid valve, metal, servo assisted

Control function: Normally closed

DN	Operating pressure	Air output	Connection	Voltage	Valve body material	Seal material
4	1.5 to 10 bar	0.7 m <sup>3</sup> /h at 6 bar	Threaded sockets	24 V DC 24 V AC 230 V AC 50Hz	Aluminium	NBR
7	1 to 10 bar	1.4 m <sup>3</sup> /h at 6 bar				



### **GEMÜ 8506 NAMUR**

**3/2, 5/2-way solenoid valve, metal, servo assisted**

Control function: Normally closed

DN	Operating pressure	Air output	Connection	Voltage	Valve body material	Seal material
6	2 to 8 bar	1.2 m <sup>3</sup> /h at 6 bar	Threaded sockets	24 V DC 24 VAC 230 VAC 50Hz	Aluminium	NBR