

STRAINERS

Y333 Y Type Strainer - Flanged

Pressure rating 16 bar (DN200 10 bar). Max temp. 100°. GJL Cast Iron Epoxy Coated Int/Ext Water Filters. DN40 to 65 / GJS Ductile Iron Epoxy Coated Int/Ext Dn80 to 400°. Stainless Steel Strainer. Internal / External Epoxy Coating. Delivered with Plug G 1/2" (DN40 to 150) and G 3/4" (DN200 to 400).



TYPE	PRODUCT CODE	SIZE	MICRON	FLANGE
Y333	149B3261	DN50	500	PN10/16
Y333	149B3262	DN65	800	PN10/16
Y333	149B3263	DN80	1250	PN10/16
Y333	149B3264	DN100	1250	PN10/16
Y333	149B3265	DN125	1250	PN10/16
Y333	149B3266	DN150	1250	PN10/16
Y333	149B23119	DN200	1250	PN16



DN "	MM	A MM	C MM	D MM	MESH MM	WEIGHT KG
2	50	230	145	50	0,50	8,5
2 1/2	65	290	137	65	0,80	9.8
3	80	310	159	75	1,25	13,5
4	100	350	187	90	1,25	18
5	125	400	249	125	1,25	27,5
6	150	480	301	170	1,25	43
8	200	600	403	220	1,60	112

